

(2) TWO ROWS 3M TWO SIDED TAPE (VHB-4956),  
CONTINUOUS @ 3/8" (9.525 mm) FROM CENTER  
EACH SIDE W/ ARCOPLAST STRUCTURAL  
ADHESIVE (A-2020) CENTERED  
DIRECTLY BEHIND JOINT

NEW OR EXIST. STRUCTURE

POSITION TAPE/SEALANT BEHIND  
PANEL JOINTS FOR RIGIDITY

ARCOPLAST 3/16" (5 mm) GFRP  
MODULAR WALL PANEL

TEMPORARY 2x4 STRIPPING TO BE ATTACHED  
AT ALL PANEL JOINTS (TYP. 4'-0" (1.2m) O.C.)  
ATTACHED WITH SCREW THAT IS APPLICABLE TO  
STRUCTURE AND LONG ENOUGH TO HOLD  
AS REQUIRED @ 24" (60 cm) O.C.

1/2" WIDE 3M TWO SIDED TAPE (VHB-4956) W/  
CONTINUOUS BEAD OF ARCOPLAST STRUCTURAL  
ADHESIVE (A-2020), SIDE BY SIDE, ADHESIVE SHALL  
BE LOCATED AT 16" (40.6 cm) O.C.

FULL TROWELED ADHESIVE PUTTY

REMOVE 2x4 STRIPPING  
AND SCREWS TO EXPOSE  
PANEL JOINT AFTER  
12 HOUR CURING TIME

FINISH PANEL JOINT WITH  
ARCOPLAST BIO-SEAL (A-1010)  
WHITE FINISHING COMPOUND

**GFRP WALL PANEL (5.0 MM), TEMPORARY WALL ATTACHING ASSEMBLY**

DWG # PP-22	SCALE 6" (1:2)
DATE 2/20/2020	CHECKED GB



1873 WILLIAMSTOWN DRIVE  
ST. PETERS, MISSOURI USA 63376  
T: 888-736-2726 F: 636-978-7782

WWW.ARCOPLAST.COM