



1/8" (3 mm) THICK X 5/8" (15.9 mm) WIDE ARCOPLAST ANODIZED ALUMINUM FLAT BAR "SPACER" & DIFFERENT THICKNESS 3M TWO SIDED TAPE TO ALLOW DIFFERENT THICKNESS OF TEMPERED GLASS, CONSULT WITH ARCOPLAST FOR FURTHER INFORMATION AND METHODS OF CONSTRUCTION

316 POLISHED STAINLESS STEEL WINDOW FRAME, DEPTH OF GLASS REST TO BE PER GLASS THICKNESS AND OR JOB REQUIREMENTS

1/8" (3 mm) THICK X 5/8" (15.9 mm) WIDE ARCOPLAST ANODIZED ALUMINUM FLAT BAR "SPACER"

3/8" (9.5 mm) TEMPERED GLASS, MEASURE, CUT AND SET AFTER FRAME IS INSTALLED

ARCOPLAST TWO-COMPONENT ARCOPLAST STRUCTURAL ADHESIVE

DOUBLE METAL STUDS @ WINDOW ROUGH OPENING (CONSULT ARCOPLAST & STRUCTURAL FRAMING REQUIREMENTS PER ARCHITECT/ENGINEER)

DRYWALL (OR OTHER WALL PANEL)

DRYWALL SCREW ALONG DOOR ROUGH OPENING 1.25" (31.76 mm) @ 12" (30 cm) O.C. (TYP.)

ARCOPLAST 1/2" (12.5 mm) ENGINEERED POLYMER WALL PANEL

3M TWO SIDED TAPE (VHB-4959), ALTERNATE EVERY 12" (30 cm) W/ BEAD OF ARCOPLAST STRUCTURAL ADHESIVE

**ENGINEERED POLYMER WINDOW GLAZING & FRAME DETAIL, STAINLESS STEEL FRAME**

DWG # <b>WF-10-EP</b>	SCALE <b>6" (1:2)</b>
DATE <b>3/6/17</b>	CHECKED <b>GB</b>



1873 WILLIAMSTOWN DRIVE  
ST. PETERS, MISSOURI USA 63376  
T: 888-736-2726 F: 636-978-7782

WWW.ARCOPLAST.COM