

DRYWALL "L" TRIM PIECE TO FINISH OF CORNER

DOUBLE METAL STUDS @ WINDOW ROUGH OPENING
(CONSULT ARCOPLAST & STRUCTURAL FRAMING REQUIREMENTS PER ARCHITECT/ENGINEER)

1/8" (3 mm) THICK X 5/8" (15.9 mm) WIDE ARCOPLAST ANODIZED ALUMINUM FLAT BAR "SPACER" & DIFFERENT THICKNESS 3M TWO SIDED TAPE TO ALLOW DIFFERENT THICKNESS OF TEMPERED GLASS, CONSULT WITH ARCOPLAST FOR FURTHER INFORMATION AND METHODS OF CONSTRUCTION

DRYWALL (OR OTHER WALL PANEL)

ARCOPLAST EXTRUDED ALUMINUM GLAZING SPLINE

1/2" (12.7 mm) WIDE 3M TWO SIDED TAPE (VHB-4936)

PANCAKE HEAD FRAMING SCREW, #8 x 0.625" (15.88 mm) @ 12" (30 cm) O.C. (TYP.)

1/8" (3 mm) THICK X 5/8" (15.9 mm) WIDE ARCOPLAST ANODIZED ALUMINUM FLAT BAR "SPACER"

ARCOPLAST 1/2" (12.5 mm) ENGINEERED POLYMER WALL PANEL

1/2" (12.7 mm) WIDE 3M TWO SIDED TAPE (VHB-4956)

3/8" (9.5 mm) TEMPERED GLASS, MEASURE, CUT AND SET AFTER FRAME IS INSTALLED

1/4" MIN.
(6.4 mm)

3M TWO SIDED TAPE (VHB-4959), ALTERNATE EVERY 12" (30 cm) W/ BEAD OF ARCOPLAST STRUCTURAL ADHESIVE

ARCOPLAST TWO-COMPONENT ARCOPLAST STRUCTURAL ADHESIVE

ENGINEERED POLYMER WINDOW GLAZING & FRAME DETAIL, ONE SIDE OF WALL

DWG #
WF-6-EP

SCALE
6" (1:2)

DATE
3/6/17

CHECKED
GB/KAW



1873 WILLIAMSTOWN DRIVE
ST. PETERS, MISSOURI USA 63376
T: 888-736-2726 F: 636-978-7782

WWW.ARCOPLAST.COM